









Declaration of Performance

PROD-DOP-SENSE (EN)

1. Unique identification code of the product-type:
SPC / rigid vinyl plank of stone plastic composite in accordance with EN 14041:2004/AC:2006 with a thickness between 3,2-6,0mm and density round 2.000kg/m³. SENSE F/G/W-series
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 par 4*:
Type and batch number mentioned on the label on the box.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
For use as wall covering in buildings according to the Prodinex specifications.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 par 5*:
Sense by Prodinex BV, Ommelseweg 67, 5721 WT Asten (NL)
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 par 2*: N.A.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V*: System 3
7. Name and identification number of the notified body, in case of the declaration of performance concerning a construction product covered by a harmonised standard:
Intertek NB1023; report no 190801008SHF
8. Name and identification number of the Technical Assessment Body, in case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued: N.A.
9. Declared performance

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
Reaction to fire		EN 14041:2018 EN13501-1
Formaldehyd Emissions		EN 14041:2018 EN171-1:2004
Slip resistance		EN 14041:2018 EN13893:2002
Resistance to staining	 no change	EN 438-2:2016
Thermal resistance	 0,126 W/mK	EN 12664:2001
Static electrical propensity	 0,4 kV (rubber)	EN 1815:2016

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: R. Seelen
Function: Director

Place: Asten
Date: 01-01-2020

.....